

BLISTERSTOP

BREATHABLE FLOORING

Description

BLISTERSTOP infiltrates deep into the pores of mineral soils, making sure to fill them completely and creating a thin, shiny layer on the surface. Once hardened, this layer prevents substances containing water or oil from penetrating the pores, offering highly effective protection against stains. Even substances that remain on the surface for a long time can be removed without leaving stains.

Properties

- Résistant à l'abrasion
- Améliorer la couleur
- Polissable
- Résistant à la chaleur
- Retardateur de flamme
- Antidérapant

Technical data

Consumption	0,10 kg / m ²
Minimum application temperature	0°C
Drying	24 h. (20°C, 60% H.R)
UV resistance	High
VOC	0,5%

Application

The surfaces to be protected must be clean and dry.
It can be applied with a brush, roller and airless.

Application of two coats is recommended.

Storage

BLISTERSTOP is presented in airtight and approved containers in accordance with EU guidelines for the packaging and storage of chemical products. Avoid frost and temperatures above 35° C. The product can be stored for one year in original, closed containers and covered places.

Precautions

In case of contact with eyes, wash them with plenty of clean water and consult a doctor. Hands and skin should be washed with soap and hot water. Avoid release to the environment.

PULSATIA S.L.

Calle Benifaio, 38.46610 Guadassuar (Valencia)
Telf. +34 96 116 38 84 hello@lunik.cc

2

www.lunik.cc

The indications and technical data that appear in this brochure are based on our current knowledge and on the most typical uses and applications of the product and are indicative in nature, and may be subject to changes and modifications without prior notice. Depending on the conditions of installation, in which we have no participation, the specific values may undergo certain variations, as well as due to normal differences in manufacturing tolerances, tests carried out, etc. For this reason, our guarantee is limited only to the quality of the product supplied.